

SECONDARY CONNECTION CABINET



APPROVED



STANDARD FEATURES

Ampacities available are 1200, 2000, 3000 and 4000.

Short-circuit rating of 100kAIC @ 480VAC.

Type 3R construction standard.

Open bottom for pad mounting.

Fabricated from 12 gauge cold rolled steel.

Lifting eyes. Hinged double doors with padlockable handle and door hold open devices.

Hasp and staple for utility seal.

Line in and load out of the bottom.

Other configurations are available.

Powder coated RAL 6020 Dark Green. Custom colors are available.

Standard three-phase/four wire configuration. Custom configurations are available single-phase/three wire and three-phase/three wire.

Lugs not included as standard. Lug kits are available, please consult factory for pricing or for special lug requirements.

Drawings are available, please consult factory.

OPTIONS

Other environmentally rated enclosures are available.

Various Lug types are available.

Custom paint colors. Custom line in and load out configurations.

APPROVALS

UL listed termination boxes.

Units can be CUL listed, consult factory if required.

Units requiring CUL listing must be specified at time of order.



HEADQUARTERS

6692 Fig Street
Arvada, Co 80004

Phone: 303.431.0111
Fax: 303.424.2040

EASTER-OWENS.COM

CONTACT US FOR PROJECT
REFERENCE INFORMATION



CALL TOLL FREE: 1.866.204.3707